FIRE / SWICKE BARRIER DESIGNATIONS
THE SYMBOLS SHOWN ARE FOR THE CONVIENIENCE OF THE CONTRACTOR. THE CONTRA SHALL VERIFY RATINGS WITH THE LATEST SET OF ARCHITECTURAL PLANS AND FURNISH MATERIALS REQUIRED TO COMPLY WITH THOSE RATINGS WHETHER SHOWN OR NOT.

1 HOUR FIRE BARRIER _____

FIDE / SMOKE BADDIED DESIGNATIONS

RACTOR ALL FLOOR ASSEMBLIES SHALL BE DESIGNATED AS 2 HOUR FIRE, BARRIER(S), UNLESS NOTED

OTHERWISE ON THE PLANS. RATINGS WERE ACQUIRED FROM THE ARCHITECTURAL PLANS.

2 HOUR FIRE BARRIER _____ SMOKE BARRIER

MECHANICAL DEMOLITION NOTES: THE DRAWINGS ARE INTENDED TO INDICATE THE SCOPE OF DEMOLITION WORK REQUIRED AND DO NOT INDICATE EVERY PIPE, DUCT, OR PIECE OF EQUIPMENT THAT MUST BE REMOVED. ACCESSIBILITY OF EQUIPMENT AND SYSTEMS IS NOT SHOWN NOR SHOULD IT BE INFERRED. THE CONTRACTOR SHALL VISIT THE SITE PRIOR TO SUBMITTING A BID AND VERIFY EXISTING CONDITIONS. CONTRACTOR IS RESPONSIBLE FOR ALL COST ASSOCIATED WITH CEILING SYSTEM DISASSEMBLY AND REASSEMBLY TO ACCOMMODATE THIS WORK. CONTRACTOR TO SALVAGE, STORE, AND REINSTALL ALL CEILING MOUNTED DEVICES. CONTRACTOR TO COORDINATE WITH OWNER FOR ALL MECHANICAL SERVICE OUTAGES. EXISTING WATER SYSTEM: MAINTAIN EXISTING SYSTEM IN SERVICE UNTIL

NEW SYSTEM IS COMPLETE AND READY FOR SERVICE. DRAIN SYSTEM ONLY TO MAKE SWITCHOVERS AND CONNECTIONS. OBTAIN PERMISSION FROM OWNER AT LEAST 72 HOURS BEFORE PARTIALLY OR COMPLETELY DRAINING SYSTEM. MINIMIZE OUTAGE DURING OPERATION. CONTRACTOR IS RESPONSIBLE FOR PATCHING ALL PENETRATIONS CREATED BY REMOVAL OF EQUIPMENT, DUCTWORK, PIPING, ETC. TO MATCH EXISTING. REPAIR ADJACENT CONSTRUCTION AND FINISHES DAMAGED

DURING DEMOLITION AND EXTENSION WORK, PATCH TO MATCH ORIGINAL CONSTRUCTION. VERIFY ALTERNATIVE OR SPECIAL REPAIR METHODS WITH ARCHITECT/ENGINEER BEFORE PROCEEDING WITH DEMOLITION. CONTRACTOR IS RESPONSIBLE FOR ALL MODIFICATIONS TO THE EXISTING HVAC PIPING AND DUCTWORK

NECESSARY TO PERMIT THE INSTALLATION OF NEW PROVIDE TEMPORARY CONNECTIONS TO MAINTAIN EXISTING SYSTEMS IN SERVICE DURING CONSTRUCTION. WHEN WORK MUST BE PERFORMED ON OPERATING EQUIPMENT, USE PERSONNEL EXPERIENCED IN SUCH OPERATIONS. EXTEND EXISTING INSTALLATIONS USING MATERIAL AND METHODS COMPATIBLE WITH EXISTING MECHANICAL INSTALLATIONS, OR AS SPECIFIED FOR INTENDED

ALL SYSTEM CHANGEOVERS BE COMPLETED IN OVERTIME, NOT DURING NORMAL WORKING HOURS. D. REMOVE, RELOCATE, AND EXTEND EXISTING INSTALLATIONS TO ACCOMMODATE NEW CONSTRUCTION.

1. REMOVE ABANDONED DUCTS AND PIPING TO SOURCE OF SUPPLY AND/OR MAIN LINES AND CAP OR MAKE READY FOR RECONNECTION IF SERVICE IS EXTENDED AS PART OF NEW WORK. 2. DISCONNECT AND REMOVE MECHANICAL DEVICES AND EQUIPMENT SERVING EQUIPMENT THAT HAS BEEN REMOVED.

3. MAINTAIN ACCESS TO EXISTING MECHANICAL

OPERATIONAL.

INSTALLATIONS WHICH REMAIN ACTIVE. MODIFY

INSTALLATION OR PROVIDE ACCESS PANEL AS APPROPRIATE. 4. MECHANICAL ITEMS REMOVED AND NOT RELOCATED REMAIN THE PROPERTY OF THE OWNER. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE DISPOSAL OF MATERIAL THE OWNER DOES NOT WANT TO REUSE OR RETAIN FOR MAINTENANCE PURPOSES. 5. MECHANICAL CONTRACTOR IS RESPONSIBLE FOR BLEEDING AIR THAT MAY HAVE ENTERED THE SYSTEM DURING CONSTRUCTION FROM EXISTING AND NEW PIPING BEFORE WATER SYSTEMS BECOME

GENERAL MECHANICAL NOTES: DRAWINGS SHOWING LOCATIONS OF EQUIPMENT, DUCTWORK, PIPING, ETC. ARE DIAGRAMMATIC AND MAY NOT ALWAYS REFLECT ACTUAL INSTALLATION CONDITIONS. DRAWINGS SHOW THE GENERAL ARRANGEMENT OF ALL DUCTWORK, PIPING, EQUIPMENT, ETC., AND MAY NOT INCLUDE ALL OFFSETS AND FITTINGS REQUIRED FOR COMPLETE INSTALLATION. THE DRAWINGS SHALL BE FOLLOWED AS CLOSELY AS ACTUAL BUILDING CONSTRUCTION AND THE WORK OF OTHERS WILL PERMIT. DO NOT SCALE DRAWINGS. VERIFY ALL DIMENSIONS AND CLEARANCES FROM ARCHITECTURAL, STRUCTURAL, SUBMITTALS, AND OTHER APPROPRIATE

DRAWINGS OR PHYSICALLY AT SITE. READ ALL SPECIFICATIONS. REVIEW ALL DRAWINGS, INCLUDING THOSE OF OTHER TRADES. LAYOUT AND COORDINATE ALL WORK WITH ALL OTHER TRADES PRIOR TO INSTALLATION TO PROVIDE CLEARANCES REQUIRED FOR OPERATION, MAINTENANCE, CODE COMPLIANCE, AND TO VERIFY NON-INTERFERENCE WITH OTHER WORK. DO NOT FABRICATE PRIOR TO VERIFICATION OF NECESSARY CLEARANCES FOR ALL TRADES. BRING ANY INTERFERENCES OR CONFLICTS TO THE ATTENTION OF THE ARCHITECT/ENGINEER BEFORE PROCEEDING WITH ANY FABRICATION OR EQUIPMENT ORDERS. CONTRACTOR IS RESPONSIBLE FOR REVIEW OF

SPACE REQUIREMENTS OF EQUIPMENT SPECIFIED OR SUBSTITUTED AND MAKING REASONABLE ACCOMMODATIONS IN LAYOUT AND POSITIONING TO PROVIDE PROPER ACCESS. ANY CHANGES THAT ARE REQUIRED TO ELIMINATE CONFLICTS AND RESULT FROM A FAILURE TO COORDINATE SHALL BE MADE BY THE CONTRACTOR WITHOUT ADDITIONAL COST OR EXPENSE TO THE CAULK ALL PIPE AND DUCT PENETRATIONS OF FULL

PREVENT NOISE TRANSMISSION FROM ONE ROOM TO ANOTHER AND TO PROVIDE THE DESIRED NC LEVELS WITHIN THE ROOMS. CONTRACTOR IS RESPONSIBLE FOR ALL COST ASSOCIATED WITH ELECTRICAL CHANGES REQUIRED FOR EQUIPMENT DIFFERENT THAN THE BASIS OF

AND ROOF ASSEMBLIES. THIS IS ESSENTIAL TO

HEIGHT NON FIRE RATED WALLS, PARTITIONS, FLOORS

DESIGN. REFER TO ARCHITECTURAL REFLECTED CEILING PLAN FOR EXACT LOCATIONS OF ALL CEILING MOUNTED DEVICES. TERMINAL AIR BOX (TAB) NUMBER OR REHEAT COIL NUMBER IS SHOWN ADJACENT TO THERMOSTAT ONLY

WHEN THE TAB OR COIL WHICH THE THERMOSTAT IS CONTROLLING IS AMBIGUOUS. . ALIGN LIGHT SWITCHES AND TEMPERATURE SENSORS WHEN IN CLOSE PROXIMITY TO EACH OTHER. . PROVIDE ACCESS DOORS AT ALL DUCT MOUNTED EQUIPMENT.

DESIGN CODES:	
DESCRIPTION:	YEAR:
INTERNATIONAL BUILDING CODE	2012
INTERNATIONAL MECHANICAL CODE	2012
INTERNATIONAL PLUMBING CODE	2012
INTERNATIONAL FIRE CODE	2012
INTERNATIONAL ENERGY CONSERVATION CODE	2012

CONTACT PERSONS DESCRIPTION: PERSON: PROJECT MANAGER DAVID LARSON MECHANICAL ENGINEER NATE JACQUES

	EXISTING TO BE REMOVED
	NEW COLD WATER BOTABLE
	COLD WATER - POTABLE CHILLED WATER RETURN
	CHILLED WATER SUPPLY
COND	CONDENSATE (GRAVITY DRAIN)
D	DRAIN LINE
	HEATING WATER RETURN
	HEATING WATER SUPPLY
	LOW PRESSURE CONDENSATE
——V——	PUMPED CONDENSATE
	STEAM - NUMBER INDICATES PRESSURE IN PSIG.
	NON-POTABLE COLD WATER
	PIPE CAP
	PIPE DOWN
 0	PIPE UP OR UP/DOWN
	PITCH PIPE IN DIRECTION
	DIRECTION OF FLOW IN PIPE
	NEW CONNECTION
	UNION/FLANGE
── ₩	SHUTOFF VALVE NORMALLY OPEN
→	SHUTOFF VALVE NORMALLY CLOSED
——₩ ——₩ ^{0.5}	THROTTLING VALVE (NO. INDICATES CDM)
——————————————————————————————————————	BALANCING VALVE (NO. INDICATES GPM) CONTROL VALVE (TWO-WAY)
	CHECK VALVE
% □	
☆ ♦	SAFETY/RELIEF VALVE
▶	PRESSURE REDUCING VALVE (LIQUID/GAS)
<u> </u>	PRESSURE REDUCING VALVE (STEAM)
Y	VACUUM BREAKER
 }	"WYE" - STRAINER
- No.	"WYE" - STRAINER W/SHUTOFF VALVE AND HOSE CONNECTION WITH CAP
	FLEXIBLE CONNECTION
	PRESSURE/TEMPERATURE TEST PLUG
D	REDUCER - REFERENCE SPECIFICATION FOR CONCENTRIC/ECCENTRIC AND FOT/FOB
M	METER
— ⋈ —®	PRESSURE GAUGE (FURNISHED WITH BALL VALVE)
<u> </u>	SUCTION DIFFUSER WITH SUPPORT FOOT
-	AUTOMATIC AIR VENT
1	MANUAL AIR VENT W/ BALL VALVE
↑	
Ŧ	DRAIN VALVE WITH HOSE CONNECTION, CAP AND BALL VALVE
<u></u> _	TRIPLE DUTY VALVE
	TEMPERATURE SENSOR WITH WELL
<u>U</u>	THERMOMETER WITH WELL (FILLED TYPE)
<u> </u>	FLOW SWITCH
FM	
- T-	FLOW METER
D_{τ}	F&T STEAM TRAP (REFER TO SCHEDULE)
レ <u>!-*</u> 	INVERTED BUCKET STEAM TRAP
<u>T-*</u>	(REFER TO SCHEDULE) ALIGNMENT GUIDE
×	PIPE ANCHOR
	EXPANSION JOINT
_ ①	THERMOSTAT/SENSOR
\bigcirc	PUMP
(WM)	WATER METER
DP	DIFFERENTIAL PRESSURE SWITCH
CS	CURRENT SWITCH
FM	FLOW METER
CP	CONDUCTIVITY PROBE
AI	ANALOG INPUT
X	
(AO)	ANALOG OUTPUT
X	
(DI)	DIGITAL INPUT
$\dot{\wedge}$	DIGITAL OUTDUT
(DO)	DIGITAL OUTPUT
AD	ACCESS DOOR
AFF	ABOVE FINISHED FLOOR
E.C.	ELECTRICAL CONTRACTOR
FCU	FAN COIL UNIT
G.C.	
H.C.	HEATING CONTRACTOR
M.C.	MECHANICAL CONTRACTOR
NC N.C.	NEW CONNECTION NORMALLY CLOSED
N.C. N.O.	NORMALLY CLOSED NORMALLY OPEN
P.C.	PLUMBING CONTRACTOR
1 .0.	
PS	PRESSURE SWITCH

PIPING SYMBOLS LIST

SYMBOL: DESCRIPTION:

		CONSULTANTS:
		HEALTHCARE PLANNERS: VOA ARCHITECTS MEPFP + TECH + STRUCT: KJWW CONSULTING ENGINEERS CIVIL ENGINEER: JD ENGINEERING COST ESTIMATING: MOSS CONSTRUCTION COST MANAGEMENT
Revisions:	Date	INDUSTRIAL HYGIENE: JOHN A. JURGIEL & ASSOCIATES, INC.


VA FORM 08-6231, OCT 1978



Drawing Title	Project Title RENO	Project Number 549-130							
PIPING COVER SHEET	SAM RA	SAM RAYBURN MEMORIAL VETERANS CENTER							
Approved: Project Director	Location BONHAM, TEXAS			Drawing Number					
	Date	Checked	Drawn	MP001					
	APRIL 13, 2015	LINPEA	NATJAC	Dwg. 72 of 14	42				

GENERAL NOTES:


1. EXISTING CONDITIONS ARE SHOWN BASED ON FILED OBSERVATIONS AND EXISTING DOCUMENTS. CONTRACTOR SHALL FIELD VERIFY CONDITIONS AND CONTACT ENGINEER IF ANY DISCREPANCIES ARISE PRIOR TO COMPLETING WORK.



	CONSULTANTS:	ARCHITECT:	Drawing Title BASEMENT FLOOR PLAN - PIPING -	Project Title RENOVATE AND EXPAND AMBULATORY CARE AND LAB.	Project Number 549-130	Office of
	HEALTHCARE PLANNERS: VOA ARCHITECTS MEPFP + TECH + STRUCT: KJWW CONSULTING ENGINEERS	MICHAEL ROTH & ASSOCIATES.	DEMO		Building Number 1	Office of Facilities
	CIVIL ENGINEER: JD ENGINEERING COST ESTIMATING: MOSS CONSTRUCTION COST MANAGEMENT	ARCHITECTS & PLANNERS, INC. 200 SOUTH HANLEY ROAD, STE. 1105, CLAYTON, MISSOURI 63105, 314-862-2112	Approved: Project Director	Location BONHAM, TEXAS Date Checked Drawn	Drawing Number MP101	Management
Revisions: Date	INDUSTRIAL HYGIENE: JOHN A. JURGIEL & ASSOCIATES, INC.	200 3001111/(NELT ROAD, STE. 1103, CEATTON, MISSOURI 03103, 014-002-2112		APRIL 13, 2015 LINPEA NATJAC	Dwg. 73 of 142	Department of Veterans Affairs


1 2 5

VA FORM 08-6231, OCT 1978



GENERAL NOTES:

1. REFER TO 7/MP301 FOR SAFTY VALVE DISCHARGE PIPING DETAIL.
2. REFER TO 8/MP301 FOR STEAM MAIN DRIP CONNECTION DETAIL.
3. REFER TO MP401 AND MP402 FOR FLOW DIAGRAMS AND MP501 FOR PIPING SCHEDULES.
4. REFER TO MP601 FOR CONTROL DIAGRAMS.
5. REFER TO 1/MP302 FOR ALIGNMENT GUIDE DETAIL.
6. REFER TO 2/MP302 FOR PIPE ANCHOR DETAIL.







1 2 5 5

VA FORM 08-6231, OCT 1978


	CONSULTANTS:	ARCHITECT:	Drawing Title	Project Title RENOVATE AND EXPAND AMBULATORY CARE AND LAB.	Project Number 549-130	
	HEALTHCARE PLANNERS: VOA ARCHITECTS MEPFP + TECH + STRUCT: KJWW CONSULTING ENGINEERS	MICHAEL ROTH & ASSOCIATES,	BASEMENT FLOOR PLAN - PIPING		Building Number 1	Office of Facilities
	CIVIL ENGINEER: JD ENGINEERING COST ESTIMATING: MOSS CONSTRUCTION COST MANAGEMENT	ARCHITECTS & PLANNERS, INC. 200 SOUTH HANLEY ROAD, STE. 1105, CLAYTON, MISSOURI 63105, 314-862-2112	Approved: Project Director	Location BONHAM, TEXAS Date Checked Drawn	Drawing Number MP103	Management
Revisions: Date	INDUSTRIAL HYGIENE: JOHN A. JURGIEL & ASSOCIATES, INC.	200 300111 HANLLI KOAD, SIE. 1103, CLATION, MISSOURI 63103, 314-662-2112		APRIL 13, 2015 LINPEA NATJAC	Dwg. 75 of 142	Department of Veterans Affairs






VA FORM 08-6231, OCT 1978

100% ISSUED FOR CONSTRUCTION






ENLARGED LABORATORY FLOOR PLAN - PIPING

1/8" = 1'-0"

VA FORM 08-6231, OCT 1978





ENLARGED SECURITY FLOOR PLAN - PIPING

1/8" = 1'-0"

	CONSULTANTS:	ARCHITECT:	Drawing Title ENLARGED FLOOR PLAN -	Project Title RENOVATE AND EXPAND AMBULATORY CARE AND LAB. Project Numb 549-130	
	HEALTHCARE PLANNERS: VOA ARCHITECTS MEPFP + TECH + STRUCT: KJWW CONSULTING ENGINEERS	MICHAEL ROTH & ASSOCIATES,	LABORATORY AND SECURITY - PIPING	SAM RAYBURN MEMORIAL VETERANS CENTER Building Num 1	Facilities
	CIVIL ENGINEER: JD ENGINEERING COST ESTIMATING: MOSS CONSTRUCTION COST MANAGEMENT	ARCHITECTS & PLANNERS, INC.	Approved: Project Director	Location BONHAM, TEXAS Date Checked Drawn Drawing Num MP1	
Revisions:	INDUSTRIAL HYGIENE: JOHN A. JURGIEL & ASSOCIATES, INC.	200 SOUTH HANLEY ROAD, STE. 1105, CLAYTON, MISSOURI 63105, 314-862-2112		APRIL 13, 2015 LINPEA NATJAC Dwg. 78	of 142 Department of Veterans Affairs


2 5 7





CHILLER UNIT SUPPORT

1. PROVIDE FULL PERIMETER CURB WITH SHEET METAL CAP AND SEAL WATER-TIGHT.





- INSULATION SHIELD (TYP.)

VA FORM 08-6231, OCT 1978

NOTES:

1. REFER TO SPECIFICATION SECTIONS 23 05 11 & 23 07 11.

IN SPEC SECTION 23 05 29, STEEL SADDLE FILLED WITH INSULATION.

— UNI-SIRUT OR EQUIVALENT

NOTE 3

TRAP CONNECTION SIZE OR 3/4", WHICHEVER IS LARGER

DIRT LEG

THREADED CAP
OR BLIND FLANGE

STRAINER WITH
BLOWDOWN VALVE


VALVE FOR TESTING TRAP.

2 STEAM MAIN DRIP CONNECTION

NOTES:

1. DRIP AND DIRT LEGS SHALL BE AT LEAST TWICE THE DIAMETER OF THE TRAP INLET.


- 2. INSTALL LEGS OF STRAINERS IN HORIZONTAL POSITION TO MINIMIZE CONDENSATE HOLDING.
- 2. INSTALL LEGS OF STRAINERS IN HORIZONTAL POSITION TO MINIMIZE CONDENSATE HOLDING.
- 3. TEE SHALL BE FULL SIZE FOR 4" AND SMALLER MAINS.
- 4. LOCATE DRIP TRAPS AT 300 FOOT MAXIMUM INTERVALS AND UPSTREAM OF ALL EXPANSION DEVICES, BRANCH CONNECTIONS OR CONTROL VALVES.



5 FLASH AND CONDENSATE TANK VENT DISCHARGE PIPING

NOTES:

1. LOCATE THIS DISCHARGE ON ROOF OF LOADING DOCK.



PIPE THROUGH NON-FIRE RATED WALL NO SCALE

THIS DETAIL APPLIES TO ALL PIPES. THE INTENTION IS TO CONTINUE
THE INSULATION AND VAPOR BARRIER THROUGH ALL PENETRATIONS.
PERMIT THERMAL EXPANSION WITHOUT DAMAGING INSULATION, AND
TO SEAL AIRTIGHT AROUND INSULATED AND UNINSULATED PIPES FOR
NOISE TRANSMISSION CONTROL.
 FLOOR OPENINGS ARE SIMILAR SEE SPECIFICATION SECTION 23 05 11

FOR DIFFERENCES BETWEEN FLOOR AND WALL PENETRATIONS.

3. SEE SPECIFICATION SECTION 23 05 11 FOR ADDITIONAL INFORMATION.

SLOPE STEAM PIPING BACK TO HUMIDIFIER — 3" COPPER, STAINLESS STEEL OR SCH40 STEEL PIPE HUMIDIFIER SUPPLY VALVE — STEAM TO STEAM HUMIDIFIER. PROVIDED WITH HUMIDIFIER. - INTERLOCK HUMIDIFIER DRAIN - HUMIDIFIER VALVE AND CW VALVE TO - HUMIDIFIER DRAIN MANIFOLD OPERATE IN UNISON. BALANCE VALVE PROVIDED WITHIN AHU CW TO RESULT IN A MIXED WATER TRAP DEPTH PER
MANUFACTURERS ROUTE TO -FLOOR WITH HUMIDIFIER. TEMPERATURE BELOW 140°F. REMOVABLE — RECOMMENDATIONS. PIPE DRAIN. — CITY WATER BYPASS SECTION REMOVABLE SUMMER SHUTOFF -VALVE BY CONTROLS CONTRACTOR. ROUTE TO FLOOR DRAIN. INSTALL STRAINER IN HORIZONTAL POSITION TO HOSE BIBB PREVENT CONDENSATE FROM POOLING. (TYP.) - WATER SOFTENER HUMIDIFIER STEAM CONTROL VALVE PROVIDED WITH HUMIDIFIER. TRAP DEPTH PER ---— SEE SPECIFICATION SECTION -MANUFACTURERS 22 30 00 - PLUMBING EQUIPMENT RECOMMENDATIONS. WITH FUNNEL.

6 HUMIDIFIER (STEAM TO STEAM) DETAIL

NOTES:

1. WORK IN LIGHT TEXT AND LINE WEIGHT BY PLUMBING CONTRACTOR.


CON	ISULTANTS:	ARCHITECT:	Drawing Title	Project Title RENOVATE AND EXPAND AMBULATORY CARE AND LAB.	Project Number 549-130
	THCARE PLANNERS: VOA ARCHITECTS FP + TECH + STRUCT: KJWW CONSULTING ENGINEERS	MICHAEL ROTH & ASSOCIATES,	DETAILS - PIPING		Building Number 1
CIVIL	L ENGINEER: JD ENGINEERING	ARCHITECTS & PLANNERS, INC.	Approved: Project Director	Location BONHAM, TEXAS	Drawing Number
	T ESTIMATING: MOSS CONSTRUCTION COST MANAGEMENT ISTRIAL HYGIENE: JOHN A. JURGIEL & ASSOCIATES, INC.	200 SOUTH HANLEY ROAD, STE. 1105, CLAYTON, MISSOURI 63105, 314-862-2112		Date Checked Drawn LINPEA NATJAC	MP301 Dwg. 80 of 142

Office of

Facilities

Management

Department of Veterans Affairs




UTILITY PIPE PIPE STUB ANCHOR HOLLOW CMU ANCHOR SOLID CMU/CONC. 4"Ø "HILTI HIT HY-20 RED" "HILTI HIT HY-150" 6"Ø OR LESS




TUNNELS AND CORROSIVE AREAS.


1. MATERIAL - CARBON STEEL IN DRY AREAS, ALL STAINLESS STEEL IN



PIPE ANCHOR DETAIL



HEAT EXCHANGER SUPPORT DETAIL




RATED FIRE BARRIER PENETRATION

NOTES:

THE INTENT IS TO MAINTAIN THE FIRE RATING AND TO ALLOW LONGITUDINAL MOVEMENT. REFER TO SPECIFICATION SECTION 07 84 00 AND 23 05 03 FOR SELECTION OF THROUGH PENETRATION FIRE STOPPING. 2. SCHEDULE 5 PIPE SLEEVE EMBEDDED IN WALL OR FLOOR, OR SMOOTH CORE DRILL. EACH CONTRACTOR FURNISHES SLEEVE TO G.C., COORDINATES SLEEVE LOCATIONS AND DEBURS SLEEVE. G.C. BUILDS SLEEVE INTO WALL OR FLOOR ALLOWING NO GAP AROUND SLEEVE. IF SLEEVE IS NOT PROVIDED WHEN WALL OR FLOOR IS BUILT, CONTRACTOR SHALL INSTALL SLEEVE SIZE SHALL ALLOW ANNULAR SPACE REQUIRED BY THE SELECTED FIRE


1. THIS GENERAL DETAIL APPLIES TO ALL ITEMS PENETRATING FIRE RATED WALLS OR FLOORS.

3. INSTALL BACKING MATERIAL, SUCH AS MINERAL WOOL SAFING, AS REQUIRED FOR FIRE STOP SYSTEM. INSTALL IN ACCORDANCE WITH FIRE STOP SYSTEM APPLICATION LISTING. SECURE TO WALL OR FLOOR TO ALLOW LONGITUDINAL MOVEMENT OF PENETRATING ITEM WITHOUT MOVEMENT OF FIRE BARRIER. 4. WATER-TIGHT WELDED 1"x1" 20 GAUGE MINIMUM GALVANIZED SHEET METAL ANGLE FRAME, BY CONTRACTOR IN EQUIPMENT ROOMS FOR WATER STOP. PLACE A BEAD OF WATERPROOF SEALANT BETWEEN FLOOR AND BOTTOM OF ANGLE FRAME. SECURE TO FLOOR WITH MASONRY ANCHORS IN CORNERS AND ON 12" MAXIMUM CENTERS. MULTIPLE PENETRATING ITEMS MAY BE ENCLOSED IN ONE FRAME.



ROOF PIPE SUPPORT DETAIL

1. PIPING SUPPORTS SHALL BE LOCATED DIRECTLY ON TOP OF BEAMS. COORDINATE LOCATIONS WITH GENERAL CONTRACTOR.





	CONSULTANTS:	ARCHITECT:	Drawing Title	Project Title RENOVATE AND EXPAND AMBULATORY CARE AND LAB.	Project Number 549-130	Ott: t
	HEALTHCARE PLANNERS: VOA ARCHITECTS MEPFP + TECH + STRUCT: KJWW CONSULTING ENGINEERS	MICHAEL ROTH & ASSOCIATES.	DETAILS - PIPING			Office of Facilities
	CIVIL ENGINEER: JD ENGINEERING COST ESTIMATING: MOSS CONSTRUCTION COST MANAGEMENT	ARCHITECTS & PLANNERS, INC.	Approved: Project Director	Location BONHAM, TEXAS	Drawing Number MP302	Management
Revisions: Date	INDUSTRIAL HYGIENE: JOHN A. JURGIEL & ASSOCIATES, INC.	200 SOUTH HANLEY ROAD, STE. 1105, CLAYTON, MISSOURI 63105, 314-862-2112		Date Checked Drawn APRIL 13, 2015 LINPEA NATJAC	Dwg. 81 of 142	Department of Veterans Affairs

100% ISSUED FOR CONSTRUCTION

VA FORM 08-6231, OCT 1978

1 2 5





	CHILLER SCHEDULE (AIR COOLED)																															
	NOTE: 1. REFER TO SPECIFICATION SECTION 23 05 12, 23 05 41, AND 23 64 00 FOR ADDITIONAL INFORMATION.																															
	CAPACITY/PERFORMANCE EVAPOR					VIBRATION MAX. ALLOWABLE SOUND POWER IN DB RE 10-12 EVAPORATOR PERFORMANCE ISOLATION NOTE 1 WATTS OCTAVE BAND CENTER FREQUENCY ELECTRICAL																										
						MAX. KW/	TON AT % LOAD R CONDITIONS LISTED.												DISCONNECT CONTROLLER/ STARTER				LLER/ STARTER									
TAG NAME	AREA SERVED	REFRIGERANT TYPE	DESIGN TONS	STAGES OF UNLOADING	100	75 50	25	IPLV	EWT °F	LWT °F (MAX. PRESS. FOUL PROP FT. HEAD FACT		E DEFL.	63	125	5 250	500 10	000 2	000 40	000 VO	DLTAGE	PHASES	MCA	МОСР	BY (NOTE A)	TYPE (NOTE B)	BY (NOTE A)	TYPE (NOTE C)	MANUFACTURE	MODEL	REMARKS
ACC-1	CHILLED WATER SYSTEM	R410a	113.0	4	9.6	13.5 16.3	17.2	15.1	48	40 3	340.0	15.80 0.00	010 SP	0.75	67	69	67	65 6	62	59 5	56	480	3	307.0	350	MFR	NF	MFR	FV	DAIKIN	AGZ130D	NOTE 1
ACC-2	CHILLED WATER SYSTEM	R410a	113.0	4	9.6	13.5 16.3	17.2	15.1	48	40 3	340.0	15.80 0.00	010 SP	0.75	67	69	67	65 6	62	59 5	56	480	3	307.0	350	MFR	NF	MFR	FV	DAIKIN	AGZ130D	NOTE 1

FLASH TANK SCHEDULE													
SYMBOL	AREA SERVED	INLET (IN.)	VENT (IN.)	DRAIN (IN.)	TANK HEIGHT (IN.)	MANUFACTUR ER	MODEL	REMARKS					
FT-1	ADDITIONAL				36'-0"		AFT						

	CHILLED WATER BUFFER TANK SCHEDULE												
NOTES: 1. IDE WITH 4" x 6" HANDHOLE. 2. ASME STAMPED IN ACCORDANCE WITH SECTION VIII OF THE ASME CODE. 3. PROVIDE WITH 5-YEAR WARRANTY. 4. VERTICAL CABON STEEL, HEAVY GAUGE STEEL JACKET CONSTRUCTION. 5. PROVIDE WITH DRAIN AND AIR VENT.													
TAG NAME	SERVICE	TANK CAPACITY (GALLONS)	DIMENSIONS (DIAMETER x HEIGHT)	WORKING PRESSURE	INLET/OUTLET SIZE	MANUFACTURER	MODEL	NOTES					
BT-1	CHILLED WATER SYSTEM	300	36" x 72"	125 PSIG	6" FLANGED CONNECTIONS	CHEMLINE	CWB	NOTE 1,2,3,4 & 5					
BT-2	CHILLED WATER SYSTEM	300	36" x 72"	125 PSIG	6" FLANGED CONNECTIONS	CHEMLINE	CWB	NOTE 1,2,3,4 & 5					

	SCHEDULE GENERAL NOTES:
Key Name	SCHEDULE GENERAL NOTES
A.	DISCONNECT AND CONTROLLER STARTER FURNISHED AND
	INSTALLED BY:
	MFR = MANUFACTURER
	EC = ELECTRICAL CONTRACTOR
B.	DISCONNECT TYPE:
	NF = NON-FUSED
C.	CONTROLLER STARTER TYPE:
	FV = FULL VOLTAGE
	VFD = VARIABLE FREQUENCY DRIVE
D.	NO EQUIPMENT SHALL BE SELECTED ABOVE 90% OF MOTOR
	NAME PLATE RATING.

GENERAL SHEET NOTE:

VA FORM 08-6231, OCT 1978

	UNIT HEATER SCHEDULE - HOT WATER																		
												ELEC1	RICAL						
													DISCO	NNECT	CONTROLLE	R/ STARTER			ı
								W.P.D. FT.					BY	TYPE				ļ	l
TAG NAME	AREA SERVED	CONFIGURATION	CFM	MBH	GPM	EWT °F	LWT °F	HEAD	HP	RPM	VOLTAGE	PHASES	(NOTE A)	(NOTE B)	BY (NOTE A)	CONTROL	MANUFACTURER	MODEL	NOTES
UH-1	PENTHOUSE	HORIZONTAL	900	36	3.6	180	160	0.1	0.17	1150	120	1	MFR	NF	MFR	FV	TRANE	UHS	
UH-2	PENTHOUSE	HORIZONTAL	900	36	3.6	180	160	0.1	0.17	1150	120	1	MFR	NF	MFR	FV	TRANE	UHS	·

						CC	ONDENS	ATE RE	TURN ST	ATION S	CHEDU	LE						
												ELECTRICAL						
					PUMP	RECEIVER	DISCHARGE	RECEIVER				DISCO	NNECT	CONTROLLER	STARTER			
				CONDENSATE	CAPACITY	CAPACITY	PRESSURE	PRESSURE				BY	TYPE					
TAG NAME	AREA SERVED	CONFIGURATION	LB/HR	TEMPERATURE °F	PER PUMP	GALLONS	(PSI)	RATING (PSIG)	HP PER PUMP	VOLTAGE	PHASES	(NOTE A)	(NOTE B)	BY (NOTE A)	SCCR	MANUFACTURER	MODEL	NOTE
CRS-1	NEW ADDITION	DUPLEX	2500	212 °F	12 GPM	20	30	0	3/4	120 V	1	MFR	NF	MFR	0	DOMESTIC PUMP	CC	

								PUMP S	SCH	EDULE								
			PUMP FT.			VIBRATION	ISOLATION					DISCO	NNECT	CONTROLLI	ER/STARTER			
SYMBOL	AREA SERVED	GPM	HEAD AT DESIGN	MINIMUM PUMP EFFICIENCY	INLET/IMPELL ER SIZE IN.	TYPE	DEFLECTION	HP (NOTE D)	RPM	VOLTAGE	PHASES	BY (NOTE A)	TYPE (NOTE B)	BY (NOTE A)	TYPE (NOTE C)	MANUFACTURER	MODEL	COMMENTS
CWP-1	PRIMARY LOOP	340	40	60	10.38	S	0.8	10	1150	480	3	MFR	NF	EC	FV	B&G	1510	
CWP-2	PRIMARY LOOP	340	40	60	10.38	S	0.8	10	1150	480	3	MFR	NF	EC	FV	B&G	1510	
CWP-3	SECONDARY LOOP	335	35	55	7.00	HP	-	7.5	1150	480	3	MFR	NF	EC	VFD	B&G	SERIES 80	
CWP-4	SECONDARY LOOP	335	35	55	7.00	HP	-	7.5	1150	480	3	MFR	NF	EC	VFD	B&G	SERIES 80	
HWP-1	HEATING WATER SYSTEM	150	80	68	9.00	D, W, L	-	7.5	1750	480	3	MFR	NF	EC	VFD	B&G	1510	
HWP-2	HEATING WATER SYSTEM	150	80	69	9.00	D, W, L	-	7.5	1750	480	3	MFR	NF	EC	VFD	B&G	1510	
HWP-3	AHU-1	25	25	43	5.25	HP	-	0.75	1750	480	3	MFR	NF	EC	FV	B&G	90	
HWP-4	AHU-2	25	25	43	5.25	HP	-	0.75	1750	480	3	MFR	NF	EC	FV	B&G	90	

	TRAP SCHEDULE														
	OTES: 1. CAPACITY LISTED IS FOR EACH TRAP AND INCLUDES SAFETY FACTOR. 2. SIDE INLET AND OUTLET INVERTED BUCKET TRAP. 250 PSIG RATED. CAST IRON BODY, ALL INTERNAL COMPONENTS OF STAINLESS STEEL AND REPLACEABLI IN-LINE. 3. ACCEPTABLE MANUFACTURERS ALSO INCLUDE SARCO, ARMSTRONG, HOFFMAN. REFER TO MP401 FOR TRAP PIPING DETAILS. 4.SIDE INLET AND OULET, STAINLESS STEEL FLOAT MECHANISM AND VALVE, CAST IRON BODY, BALANCED PRESSURE THERMOSTATIC AIR VENT, ALL INTERNALS REPLACEABLE IN-LINE.														
TAG NAME	AREA SERVED	TYPE	SAFETY FACTOR	SIZE	CAPACITY LB/HR (NOTE 1)	PRESSURE DIFFERENTIAL	MANUFACTURER	MODEL	NOTES						
T-1	110 PSI DRIP	I.B.	2	3/4"	10	75 PSI	SPENCE	81S	NOTES 2 & 3						
T-2	45 PSI DRIP	I.B.	2	3/4"	10	20 PSI	SPENCE	81S	NOTES 2 & 3						
T-3	HE-1, HE-2	F&T	1.25	1"	2000	0.25" W.C.	SPENCE	FTN	NOTES 3 & 4						
T-4	H-1, H-2	F&T	1.25	3/4"	350	0.25" W.C.	SPENCE	FTN	NOTES 3 & 4						
T-5	FLASH TANK	I.B.	2	3/4"	100	30 PSI	SPENCE	81S	NOTES 2 & 3						

	HEAT EXCHANGER SCHEDULE - STEAM TO WATER													
			WA	TER		STE	AM							
SYMBOL	AREA SERVED	GPM	W.P.D. FT. HEAD	EWT °F	LWT °F	PSIG (NOTE 1)	LB/HR	HEATING SURFACE FT ²	FOULING FACTOR	MANUFACTURER	MODEL	COMMENTS		
HE-1	HEATING WATER SYSTEM	150 GPM	2.2 FT	150 °F	180 °F	15	1600	32 ft²	0.001	B&G	SU			
HE-2	HEATING WATER SYSTEM	150 GPM	2.2 FT	150 °F	180 °F	15	1600	32 ft²	0.001	B&G	SU			

	PRESSURE REDUCING VALVE SCHEDULE													
TAG NAME	AREA SERVED	LB/HR	INLET PRESSURE PSI	OUTLET PRESSURE PSI	VALVE SIZE	MANUFACTURER	MODEL	NOTES						
PRV-1	ADDITION 1/3 VALVE	765	110	45	3/4"	SPENCE	E							
PRV-2	ADDITION 2/3 VALVE	1530	110	45	1 1/4"	SPENCE	E							
PRV-3	ADDITION 1/3 VALVE	765	110	45	3/4"	SPENCE	E	PROVIDE WITH SAFETY PILOT						
PRV-4	ADDITION 2/3 VALVE	1530	110	45	1 1/4"	SPENCE	E	PROVIDE WITH SAFETY PILOT						

		HUMI	DIFIER S	SCHEDUL	E - STE	AM TO	STEAM		
	= 0	R. INSTALL WATER TIC	GHT SEAL TRAP	AT DISCHARGE F	ROM HUMIDIFI	ER MANIFOLD.	NLESS STEEL PIPE BE 3. STEAM PRESSURE		1
		INE PRESS	OURE AVAILABL	E DOWNSTREAM (STE	AM GENERATO				
		THE PRESS	DISCHARGE			DR			_
SYMBOL	SERVICE	CAPACITY LB/HR			AM GENERATO	DR	MANUFACTURER	MODEL	REMARK
SYMBOL H-1	SERVICE AHU-1		DISCHARGE	STE	AM GENERATO	DR NNECT	MANUFACTURER DRISTEEM	MODEL STS	REMARKS

	HUMIDIFIER MANIFOLD SCHEDULE														
TAG NAME	SERVICE	CFM	CAPACITY LB/HR	STEAM PRESSUR (PSI)	DUCT SIZE (IN)	ABSORPTION DISTANCE MAX (IN)	MANUFACTURER	MODEL							
HM-1	AHU-1	13,000	275	5	98x54	12	DRISTEEM	ULTRA-SORB							
HM-2	AHU-2	13,000	275	5	98x54	12	DRISTEEM	ULTRA-SORE							


	CONSULTANTS:	ARCHITECT:	Drawing Title	Project Title RENOVATE AND EXPAND AMBULATORY CARE AND LAB	549-130	
	HEALTHCARE PLANNERS: VOA ARCHITECTS MEPFP + TECH + STRUCT: KJWW CONSULTING ENGINEERS	MICHAEL ROTH & ASSOCIATES.	PIPING SCHEDULES			Office of Facilities
	CIVIL ENGINEER: JD ENGINEERING COST ESTIMATING: MOSS CONSTRUCTION COST MANAGEMENT	ARCHITECTS & PLANNERS, INC.	Approved: Project Director	Location BONHAM, TEXAS Data Chacked Drawn	Drawing Number MP501	Management
Revisions: Date	INDUSTRIAL HYGIENE: JOHN A. JURGIEL & ASSOCIATES, INC.	200 SOUTH HANLEY ROAD, STE. 1105, CLAYTON, MISSOURI 63105, 314-862-2112		APRIL 13, 2015 Checked Drawn NATJAC	Dwg. 84 of 14 2	2 Department of Veterans Affairs

 1
 2


 3
 4

 5
 6

REFER TO MH501 FOR AIR HANDLER AND OTHER VENTILATION EQUIPMENT SCHEDULES.



/A FORM 08-6231, OCT 1978




TWO 100% CAPACITY HEAT EXCHANGERS AND TWO 100% CAPACITY HEATING WATER PUMPS ARE PROVIDED IN THE SYSTEM. (ONE HEAT EXCHANGER AND ONE PUMP ARE REDUNDANT). SEQUENCE OF OPERATION:
FMCS SHALL OPEN THE HEATING WATER ISOLATION CONTROL VALVE TO ASSOCIATED HEAT EXCHANGER. THE HOT WATER FLOW SWITCH SHALL PROVE FLOW THROUGH THE HEAT EXCHANGER TUBES PRIOR TO ANY STEAM BEING INTRODUCED TO THE SHELL SIDE OF THE HEAT EXCHANGER. THE STEAM CONTROL VALVES SHALL MODULATE TO THE LEAD HEAT EXCHANGER AS REQUIRED TO MAINTAIN SYSTEM SUPPLY TEMP HWS#1 AS FOLLOWS: THE 1/3 CAPACITY STEAM CONTROL VALVE SHALL BE MODULATED IN ORDER TO MAINTAIN THE HEATING WATER IF THE 1/3 CAPACITY CONTROL VALVE IS 100% OPEN AND THE HEAT EXCHANGER IS UNABLE TO MAINTAIN SETPOINT, THE 1/3 CAPACITY CONTROL VALVE SHALL CLOSE AND THE 2/3 CAPACITY STEAM CONTROL VALVE SHALL MODULATE TO MAINTAIN SETPOINT. IF THE 2/3 CAPACITY CONTROL VALVE IS 100% OPEN AND IS UNABLE TO MAINTAIN SETPOINT, THE 2/3 CAPACITY CONTROL VALVE SHALL REMAIN OPEN AND THE 1/3 CAPACITY CONTROL VALVE SHALL ALSO MODULATE OPEN TO MAINTAIN SETPOINT ON A DECREASE IN LOAD, THE 2/3 CAPACITY STEAM CONTROL VALVE SHALL REMAIN OPEN AND THE 1/3 CAPACITY STEAM CONTROL VALVE SHALL MODULATE CLOSED UNTIL SETPOINT IS ACHIEVED. ON A FURTHER DECREASE IN LOAD, THE 1/3 CAPACITY STEAM CONTROL VALVE SHALL REMAIN SHUT AND THE 2/3 CAPACITY STEAM CONTROL VALVE SHALL MODULATE CLOSED UNTIL SETPOINT IS ACHIEVED OR UNTIL IT REACHES 40% (ADJ.) OPEN. IF THE 2/3 CAPACITY STEAM CONTROL VALVE REACHES 40% (ADJ.) OPEN AND SETPOINT IS STILL NOT ACHIEVED, THE 2/3 CAPACITY STEAM CONTROL VALVE SHALL CLOSE AND THE 1/3 CAPACITY STEAM CONTROL VALVE SHALL MODULATE OPEN UNTIL SETPOINT IS ACHIEVED. FMCS SHALL LIMIT THE HWS TEMP#2 AND TEMP#3 TO MAX. 190°F (ADJ.). STEAM CONTROL VALVE OPERATION SHALL NOT BE ENABLED UNLESS FLOW IS PROVEN BY FLOW SWITCH. UPON DISABLING THE STEAM CONTROL VALVE THE HEATING WATER CONTROL VALVE SHALL BE CLOSED AFTER A 3 MINUTE (ADJ.) TIME DELAY. THE FMCS SHALL ROTATE LEAD/STANDBY HX ON A WEEKLY BASIS. INCLUDE GRAPHIC TOGGLE ON OPERATOR WORKSTATION GRAPHICAL SCREEN TO ALLOW OPERATOR TO MANUALLY SELECT WHICH HX IS LEAD AND WHICH IS STANDBY. HWS TEMP SETPOINT:
FMCS SHALL RESET THE HWS TEMP IN ACCORDANCE WITH HWS RESET SCHEDULE. **HEATING WATER PUMP CONTROL:** START/STOP: THE FMCS SHALL START THE LEAD PUMP VIA THE VFD AND SHALL RUN CONTINUOUSLY. HEATING WATER PUMPS SHALL BE STARTED AND STOPPED THROUGH A HAND-OFF-AUTO SWITCH ON THE FACE OF THE ${\sf VFD}$. WHEN PLACED IN THE HAND POSITION, PUMP MOTOR SHALL RUN CONTINUOUSLY. WHEN PLACED IN THE AUTO POSITION, THE FMCS SHALL CONTROL PUMP OPERATION. WHEN PLACED IN THE OFF POSITION, THE PUMP MOTOR THE FMCS SHALL MODULATE OUTPUT TO THE VFD AS REQUIRED TO MAINTAIN DP SETPOINT AT THE LOCATION OF THE DP TRANSMITTER. DP TRANSMITTER SIGNAL SHALL BE WIRED DIRECTLY TO THE CONTROLLER SERVING PUMP VFD (SIGNAL SHALL NOT BE TRANSMITTED ACROSS THE FMCS NETWORK.) FMCS SHALL RESET THE DP SETPOINT UNTIL ONE SYSTEM COIL MODULATING CONTROL VALVE IS 95% OPEN. IN NO CASE SHALL DP SETPOINT EXCEED 10 PSIG (ADJ) OR DROP BELOW 2 PSIG (ADJ.). THE FMCS SHALL ROTATE LEAD/STANDBY PUMPS ON A WEEKLY BASIS. INCLUDE GRAPHIC TOGGLE ON OPERATOR WORKSTATION GRAPHICAL SCREEN TO ALLOW OPERATOR TO MANUALLY SELECT WHICH PUMP IS LEAD AND WHICH IS LAG. FMCS SHALL INDICATE AN ALARM TO THE FMCS OPERATOR WORKSTATION IN THE EVENT THE FOLLOWING OCCUR: SHOULD THE FMCS COMMAND THE LEAD HW PUMP TO OPERATE AND THE PUMP FAILS TO DO SO AS DETERMINED BY THE PUMP STATUS, AN ALARM SHALL BE INDICATED AT THE FMCS OPERATOR WORKSTATION AND THE STANDBY HW PUMP SHALL AUTOMATICALLY START. AN ALARM CONDITION OCCURS AT ANY VFD. WHEN 2 GALLONS (ADJ.) OF HYDRONIC SYSTEM MAKE-UP WATER FLOWS THROUGH METER AFTER THE LAST

ACKNOWLEDGEMENT. WHEN ALARM IS MANUALLY ACKNOWLEDGED, THE FMCS SHALL RE-ZERO THE

IF SYSTEM DIFFERENTIAL PRESSURE IS NOT MAINTAINED FOR MORE THAN 15 MINUTES (ADJ.).

IF HEATING WATER SUPPLY TEMPERATURE IS MORE THAN 5°F (ADJ.) ABOVE OR BELOW SETPOINT FOR MORE

MULTIPLE HX HEATING HOT WATER CONTROL 12" = 1'-0"



FMCS SHALL CONTROL EACH VFD AS DESCRIBED IN THE SEQUENCE OF OPERATION OF THE EQUIPMENT. DRIVE SHALL BE EQUIPPED BY THE VFD MANUFACTURER WITH A COMMUNICATION CARD THAT IS COMPATIBLE WITH THE FMCS CONTROL SYSTEM. TCC SHALL PROVIDE HARD WIRING AND PROGRAMMING AS REQUIRED FOR THE FMCS TO COMMUNICATE WITH EACH VFD AS DESCRIBED THE FOLLOWING VFD CONTROL PANEL POINTS (TO INCLUDE BUT NOT LIMITED TO) SHALL BE CONTROLLED BY THE FMCS AND DISPLAYED ON THE ENGINEER CONTROL CENTER (ECC) GRAPHICAL AO - SPEED MODULATION DO - START/STOP DI - STATUS (VIA CS) DI - FAULT STATUS TCC SHALL PROVIDE A CURRENT SENSING RELAY ON ANY VFD EQUIPPED WITH A BYPASS WHERE THE VFD STATUS OUTPUT DOES NOT INDICATE THE MOTOR IS RUNNING WHEN THE VFD IS OPERATING IN ALARMS, INTERLOCKS & SAFETIES: AN ALARM SHALL BE INDICATED TO THE FMCS OPERATOR WORKSTATION IN THE EVENT A FAULT OR ERROR CONDITION OCCURS AT ANY VFD. TCC SHALL PROGRAM VFD TO ENSURE MOTOR RPM DOES NOT DROP BELOW MINIMUM REQUIRED BY MOTOR MANUFACTURER.

GENERAL CONTROL NOTES:

1. REFER TO EQUIPMENT SCHEDULES TO CROSS REFERENCE WHICH CONTROL DIAGRAMS APPLY TO WHICH ITEMS OF EQUIPMENT. EACH D.I., D.O., A.I. AND A.O. POINT SHOWN FOR ALL CONTROL DIAGRAMS SHALL BE DISCRETE FROM ALL OTHER POINTS EXCEPT AS SPECIFICALLY NOTED. ALL WIRING, CONTROL COMPONENTS, DEVICES AND PROGRAMMING SHOWN ON THESE CONTROL DRAWINGS SHALL BE PROVIDED BY THE TCC UNLESS SPECIFICALLY NOTED OTHERWISE. ALL ACTUATORS SHALL BE OF THE ELECTRICAL TYPE FOR THIS PROJECT. ALL MODULATING VALVE ACTUATORS SHOWN WITH POSITION FEEDBACK SHALL HAVE THE VALVE POSITION DISPLAYED ON GRAPHICAL SCREEN ADJACENT TO THE VALVE COMMAND SIGNAL. DISPLAYED VALVE POSITION SHALL BE FROM THE FEEDBACK DEVICE/CIRCUIT (OUTPUT SIGNAL FROM THE FMCS TO THE ACTUATOR IS NOT ACCEPTABLE) MODULATING SIGNALS SHALL BE DISPAYED AS % OPEN (SIGNALS DISPLAYED AS % CLOSED ARE NOT ACCEPTABLE) PRESSURE TRANSMITTERS WHOSE SIGNAL IS UTILIZED FOR MAINTAINING DIFFERENTIAL PRESSURE OF ANY PUMPED WATER SYSTEM (E.G. HEATING HOT WATER AND THE LIKE) SHALL BE WIRED DIRECTLY TO THE CONTROLLER WHICH MODULATES PUMP SPEED. SIGNAL SHALL BE COMPLETELY INDEPENDENT OF THE FMCS NFTWORK ALL CONTROL COMPONENTS SUCH AS RELAYS, SWITCHES, DDC CONTROLLERS, ETC. SHALL BE MOUNTED IN STEEL ENCLOSURES WITH STEEL MOUNTING BACKPLATES PER SPECIFICATION 23 09 23. EACH CONTROL PANEL SHALL HAVE A LAMINATED COPY OF THE APPLICABLE SEQUENCE OF OPERATION AND CONTROL DIAGRAM INDICATING THE POINTS, COMPONENTS AND OPERATION OF EQUIPMENT ASSOCIATED WITH EACH PANEL. REFER TO SECTION 23 09 23 FOR ADDITIONAL REQUIREMENTS. . TCC SHALL PROVIDE CONDUIT RUNS AS REQUIRED FOR OUTDOOR EQUIPMENT THAT IS BEING MONITORED OR CONTROLLED BY THE FMCS. . CONTROL DIAGRAMS ARE SCHEMATIC IN NATURE AND DO NOT SHOW ALL REQUIRED CONTROL DEVICES AND COMPONENTS. REFER TO FLOOR PLANS, FLOW DIAGRAMS AND DETAILS FOR ADDITIONAL CONTROL DEVICES, COMPONENTS AND REQUIREMENTS NOT SHOWN ON THESE CONTROL DRAWINGS. TCC SHALL PROVIDE ALL CONTROL COMPONENTS AND ACCESSORIES AS REQUIRED FOR EQUIPMENT TO BE CONTROLLED AS DESCRIBED IN THE SEQUENCE OF OPERATION REGARDLESS OF WHETHER ALL CONTROL COMPONENTS OR POINTS ARE SHOWN IN THE ASSOCIATED CONTROL DIAGRAM.

VARIABLE FREQUENCY DRIVE CONTROL - GENERAL 12" = 1'-0"

Drawing Title Project Title RENOVATE AND EXPAND ARCHITECT: **CONSULTANTS:** 549-130 AMBULATORY CARE AND LAB. Office of **CONTROL DIAGRAM - PIPING HEALTHCARE PLANNERS: VOA ARCHITECTS** SAM RAYBURN MEMORIAL **Building Number Facilities VETERANS CENTER** MICHAEL ROTH & ASSOCIATES, MEPFP + TECH + STRUCT: KJWW CONSULTING ENGINEERS Management **Approved: Project Director Drawing Number** Location **ARCHITECTS & PLANNERS, INC.** CIVIL ENGINEER: JD ENGINEERING **BONHAM, TEXAS** COST ESTIMATING: MOSS CONSTRUCTION COST MANAGEMENT Checked 200 SOUTH HANLEY ROAD, STE. 1105, CLAYTON, MISSOURI 63105, 314-862-2112 INDUSTRIAL HYGIENE: JOHN A. JURGIEL & ASSOCIATES, INC. LINPEA **APRIL 13, 2015** Veterans Affairs